



Dart Hawkesbury
1270 Aberdeen St
Hawkesbury, ON
K6A 1K7
Canada

Tel (613) 632-5200

D4732-23
Job Sheet 167678



Part No: D4732-23

Job Qty: 20 ea

Part Name: Label



Part Weight: 0 lbs

Status: Scheduled

Priority: Medium

Job Created: 11/6/17

Job Tracking No:

Due Date: 11/16/17

Created By: Chantal Lavoie

Type: Stock

Description:

Ship Via:

Bill of Materials

Job Routing

Op No	Operation	Qty	Start Date	Due Date	Standard		Workcenter/Supplier		Sign-off
					Setup hrs	Run Hrs	Workcenter / Supplier	Lead Time	
100	Purchasing	20 pcs		11/16/17	0.00	0.00	Purchasing	SP	
110	Packaging	20 pcs		11/16/17	0.00	0.00	Packaging2	SP DAS 38	
120	QC	20 pcs		11/16/17	0.00	0.00	QC6	38	DAS
130	Packaging	20 pcs		11/16/17	0.00	0.00	Packaging3	NOV 15 2017	6
140	QC21-SA	20 Ea		11/16/17	0.00	0.00	QC21		9-89

Part Op 110 - Receive & Inspect for Damage & Mat'l Certs
Descriptions: 120 - QC6- All purchased or subcontracted products
130 - Identify as per dwg & Stock Location: _____
140 - QC21- Final Inspection - Work Order Release

NOV 12 2018

MF005

DAS
21
9-89

NOV 15 2017

Job Allocations

Operation	Component Part	Required	Inventory	Allocated	Std Qty
100-Purchasing	D4732-23P	20	0	0	0

Part Specifications

Specifications could not be found.

Plex 11/6/17 8:40 AM dart.lavoie.chantal

DART
AEROSPACE
S008998



Label

Dart Aerospace Ltd.

1270 Aberdeen Street
Hawkesbury, ON K64 1K7
CANADA

TEL.: 1 613 632-5200
Email: sales@dartaero.com
www.dartaerospace.com

PART NO: D4732 - 23

Revision:


Operation:

Change No:

Purchasing

Mfg Date: 11/11/17

Job No: 167678



D4732-23 LABEL

NOTES:

- 1) MATERIAL: MAKE FROM 3M 7 MIL MASKING FILM #8522CP OR AVERY IPM #2031
ARIAL FONT WHITE LETTERS ON BLACK ADHESIVE BACK VINYL
- 2) FINISH: N/A
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: N/A
- 6) IDENTIFICATION: N/A
- 7) WEIGHT: N/A

DESIGN	RF	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN	RF		
CHECKED	<i>[Signature]</i>	DRAWING NO.	REV. B
MFG. APPR.	<i>[Signature]</i>	D4732	SHEET 12 OF 21
APPROVED	<i>[Signature]</i>	TITLE	SCALE
DE APPR.	<i>[Signature]</i>	LABELS	NTS
DATE	12.11.30	COPYRIGHT © 2012 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	

RELEASED
2013-01-30
[Signature]

studio sl2

210 Main West
Hawkesbury, Ontario K6A 2H6
Canada

INVOICE

Invoice No.: 45194
Date: 11/10/2017
Ship Date:
Page: 1
Re: Order No.

Sold to:

Dart Aerospace Ltd

1270 Aberdeen
Hawkesbury, Ontario
K6A 1K7

Ship to:

Dart Aerospace Ltd

1270 Aberdeen
Hawkesbury, Ontario
K6A 1K7

Quantity	Description	Base Price	Disc. %	Unit Price	Amount
12	D4732-1P.	6.6667		6.6667	80.00
12	D4732-3P.	6.6667		6.6667	80.00
12	D4732-5P.	6.6667		6.6667	80.00
16	D4732-7P.	6.6669		6.6669	106.67
16	D4732-9P.	6.6669		6.6669	106.67
12	D4732-11P.	6.6667		6.6667	80.00
12	D4732-13P.	6.6667		6.6667	80.00
30	D4732-15P.	6.6667		6.6667	200.00
30	D4732-19P.	6.6667		6.6667	200.00
12	D4732-21P.	6.6667		6.6667	80.00
20	D4732-23P.	6.6500		6.6500	133.00
12	D4732-25P.	6.6667		6.6667	80.00
12	D4732-29.	6.6667		6.6667	80.00
12	D4732-31P.	6.6667		6.6667	80.00
12	D4732-33P.	6.6667		6.6667	80.00
12	D4732-35P.	6.6667		6.6667	80.00
16	D4732-37P.	6.6669		6.6669	106.67
12	D4732-39P.	6.6667		6.6667	80.00
12	D4732-41P	6.6667		6.6667	80.00
PO# 038272					
Attn: Diane Baker					
Subtotal:					1,893.01
H - HST					
HST					246.10
Thank you for your business / Merci de faire affaire avec nous					
Shipped By:		Tracking Number:		HST: 825007651RT0001	
Comment: WO21383				Total Amount	2,139.11
				Amount Paid	0.00
Sold By:				Amount Owing	2,139.11



Dart Hawkesbury
1270 Aberdeen St
Hawkesbury, ON
K6A 1K7
Canada

Tel (613) 632-5200

PURCHASE ORDER PO038272

Items													
Line Item	Part	Rev	Supplier Part No	Item No	Description	Item Tax	Status	Due Date	Order Quantity	Received Quantity	Balance	Unit Price (CAD)	Extended Price
9	D4732-19P				D4732 Rev. B Label As Per Dwg D4732 Rev. B		Firmed	11/13/17	30 pcs	0 pcs	30 pcs	\$6.6666/pcs	\$200.00
Line Item Note job# 167671													
10	D4732-21P				Label As Per Dwg D4732 Rev. B		Firmed	11/13/17	12 pcs	0 pcs	12 pcs	\$6.6666/pcs	\$80.00
Line Item Note job# 167671													
11	D4732-23P				Label As Per Dwg D4732 Rev. B		Firmed	11/13/17	20 pcs	0 pcs	20 pcs	\$6.6666/pcs	\$133.33
Line Item Note job# 167678													
12	D4732-25P				Label As Per Dwg D4732 Rev. B		Firmed	11/13/17	12 pcs	0 pcs	12 pcs	\$6.6666/pcs	\$80.00
Line Item Note job# 167679													
13	D4732-29P				Label As Per Dwg D4732 Rev. B		Firmed	11/13/17	12 pcs	0 pcs	12 pcs	\$6.6666/pcs	\$80.00
Line Item Note Job# 167681													
14	D4732-31P				Label As per Dwg 4732 Rev. B		Firmed	11/13/17	12 pcs	0 pcs	12 pcs	\$6.6666/pcs	\$80.00
Line Item Note job# 167683													
15	D4732-33P				Label As Per Dwg D4732 Rev. B		Firmed	11/13/17	12 pcs	0 pcs	12 pcs	\$6.6666/pcs	\$80.00
Line Item Note job# 167684													
16	D4732-35P				Label As Per Dwg D4732 Rev. B		Firmed	11/13/17	12 pcs	0 pcs	12 pcs	\$6.6666/pcs	\$80.00
Line Item Note job# 167685													
17	D4732-37P				Label As Per Dwg D4732 Rev. B		Firmed	11/13/17	16 pcs	0 pcs	16 pcs	\$6.6666/pcs	\$106.67
Line Item Note job# 167686													
18	D4732-39P				Label As Per dwg D4732 Rev. B		Firmed	11/13/17	12 pcs	0 pcs	12 pcs	\$6.6666/pcs	\$80.00
Line Item Note job# 167688													

****CERTIFICATE of CONFORMITY****	
Customer: Studio SL2	
Purchase Order No: 038272	Packing Slip No: WIP # 21383
Description: Decals (multi)	Quantity: 284
Certification: We hereby certify that: 1. The above listed items were manufactured, repaired and/or inspected in accordance with applicable drawings and/or specifications; 2. All work was accomplished in accordance with the Dart Aerospace Purchase Order; 3. Results of all inspections, chemical or physical tests, as well as other evidence, which shows the acceptability of raw materials, parts and/or assembly components are on file and available for inspection at any time.	
Authority: 3M / 1 Year Shelf Life	
APPROVAL: Valerie Young	Signature: Val
DATE:	Title: office administrator
NOV 10, 17	

DATE 30 9-89

IJ35-10
IJ35-20**Quick Links**[3M Graphics Warranties](#)
[Technical Information Selector](#)
[Safety Data Sheets \(SDS\)](#)
[Flammability \(ASTM E84 Reports\)](#)
[Videos](#)**Product Description**

- For Solvent, Eco-Solvent UV and Latex Inkjet Printing and Screen Printing
- 3.2-mil vinyl film

Product Features

- Available in gloss and matte finishes
- Pressure-sensitive adhesive
- Permanent
- Expected Performance Life of 5 years (unwarranted period for unprinted film with no graphic protection, applied to a flat, vertical, outdoor surface)

Recommended Types of Graphics and End Uses

- Short to long-term, indoor and outdoor promotional graphics
- Signs, trade show and point-of-purchase displays
- Exhibits and architectural applications

Graphic Protection

Graphic protection can improve the appearance, performance and durability of your graphic. Always use only the graphic protection options recommended in this Bulletin for this film.

- [3M™ Scotchcal™ Gloss Overlaminate 8508](#)
- [3M™ Scotchcal™ Luster Overlaminate 8509](#)
- [3M™ Scotchcal™ Matte Overlaminate 8510](#)

Characteristics

These are typical values for unprocessed product. Processing may change the values.

Physical Characteristics

Characteristic	Value
Material	Vinyl
Film Color	White, opaque
Thickness	Without adhesive: 3.25 mil (0.081 mm) With adhesive: 4.0 mil (0.102 mm)
Adhesive	Pressure sensitive
Adhesive Color	Gray
Liner	Polyc coated paper
Flammability	ASTM E84 reports: IJ35-10 and IJ35-20 , or go to the On-line Product Catalog at 3Mgraphics.com



Bulletin Change Summary

For the most current 3M Technical Information available to successfully use this product, please view this Bulletin electronically and click on the blue underlined links to view the relevant documents.

Release J, NOV-2016:

- Updated Thickness. See "Physical Characteristics" on page 1.

3M Commercial
Solutions
3M Center
Building 220-12E-04
St. Paul, MN 55144-1000
Phone 1-888-328-3908
Web 3M.com/Graphics

3M Canada
PO Box 5757
London, ON N6A 4T1
1-800-265-1840
Fax 519-452-6245

3M México S.A. de C.V.
Av. Santa Fe No. 55
Col. Santa Fe, Del. Alvaro
Obregón
México D.F. 01210
General 5255-5270-0400
Fax 5255-5270-2277

3M Puerto Rico, Inc.
350 Chardon Avenue
Suite 1100
San Juan, PR 00918
General 787-620-3000
Fax 787-620-3018

3M and Scotchcal are trademarks of 3M Company. All other trademarks are the property of their respective owners.



Application and Installation

In addition to other 3M Bulletins specified in this document, the following Bulletins provide details that you may need to successfully apply a graphic.

- [3M Instruction Bulletin 4.22](#). Hot and Cold Roll Lamination for 3M Overlaminates.
- [3M Instruction Bulletin 5.1](#) Select and Prepare Substrates for Graphic Application
- [3M Instruction Bulletin 5.19](#). Lamination, Application & Maintenance of Floor Graphics. Complete the Surface Preparation procedure found in this Instruction Bulletin prior to applying a graphic to a surface.
- [3M Instruction Bulletin 5.5](#) Application, General Procedures for Interior and Exterior Dry Application
- [3M Instruction Bulletin 6.5](#) Storage, Handling, Maintenance, and Removal of Films and Sheetings

Pressure-sensitive Adhesive

This film has a pressure-sensitive adhesive. It bonds to the surface even with light pressure and cannot be repositioned.

Maintenance and Cleaning

Use a cleaner designed for high-quality painted surfaces. The cleaner must be wet, non-abrasive, without solvents, and have a pH value between 3 and 11 (neither strongly acidic nor strongly alkaline). See [3M Instruction Bulletin 6.5](#) for details.

Shelf Life, Storage and Shipping

Shelf Life

The shelf life is **never more than 2 years** from the date of manufacture on the original box.

If you process the film, the shelf life is changed to **1 year** from the processing date, but not later than the 2 year maximum from the manufacturing date.

Storage Conditions

- 90 °F (32 °C) maximum
- Out of sunlight
- Clean, dry area
- Original container
- Bring the film to print room temperature before using

Shipping Finished Graphics

Flat, or rolled printed side out on 5 inch (13 cm) or larger core. This helps prevent the liner, if used, from popping off.

Health and Safety



CAUTION

When handling any chemical products, read the manufacturer's container labels and the Safety Data Sheets (SDS) for important health, safety and environmental information. To obtain SDS sheets for 3M products go to 3M.com/SDS, or by mail or in case of an emergency, call 1-800-364-3577 or 1-651-737-6501.

When using any equipment, always follow the manufacturer's instructions for safe operation.

Factors that Affect Graphic Performance Life

The actual performance life of a graphic is affected by:

- the combinations of graphics materials used.
- complete ink drying or curing.
- selection, condition and preparation of the substrate.
- surface texture.
- application methods.
- angle and direction of sun exposure.
- environmental conditions.
- cleaning or maintenance methods.

Graphics Manufacturing



CAUTION

Before using any equipment, always read the manufacturer's instructions for safe operation.

Inkjet Printing

Always read and follow the ink manufacturer's written instructions on usage.

- **Sheeted film:** When used on a flat-bed inkjet printer, sheeted film may produce printing defects.
- **Ink limiting:** The recommended maximum ink limit is 250%.
- **If sheeted or stacked graphics will be stored:** If you plan to store sheeted and stacked finished graphics for an extended period of times, leave an unprinted margin (about 1/4 inch) to allow for possible shrinkage before trimming the graphic.

Do not exceed the recommended total ink coverage for the ink series used on this film. Having too high a total physical ink amount on the film results in media characteristic changes, incomplete drying, overlamine lifting, and/or poor graphic performance.

Completely Dry Graphics



IMPORTANT NOTE

Incomplete drying or curing can result in graphic failure including curling, increased shrinkage and adhesion failure, which are not covered under any 3M Graphic Warranty.

See the ink's 3M Product and Instruction Bulletin for more details.

Screen Printing

Formulations and processing conditions can affect ink durability. Refer to the Product and Instruction Bulletins for your ink for limitations and proper usage.

Cutting

See [3M Instruction Bulletin 4.1](#) for Sheeting, Scoring and Film Cutting details.

Graphic Protection

Graphic protection may improve the appearance, performance and durability of the graphic. Click on the graphic protection options listed in Product Bulletin or see the [3M Graphics Market Product Catalog](#), for more information.



IMPORTANT NOTE

During installation, scratches may occur on films without graphic protection.

Application Characteristics

Characteristic	Value
Finished Graphic Application Recommendation	Surface type: Smooth, flat and simple curved surfaces Substrate type: Metal, rigid plastic and painted surfaces Application temperature: 40° – 100°F (4° – 38°C) air and substrate Application method: Dry
Temperature Range After Application	-59 °F to +192 °F (-50 °C to +90 °C) (not for extended periods of time at the extremes)
Graphic Removal	Permanent

Warranty Information

Warranty Coverage Overview

The warranty coverage for eligible graphics is based on the user both reading and following all applicable and current 3M Graphics Product and Instruction Bulletins. The warranty period for eligible graphics is as stated in the 3M Graphics Warranties Matrices at the time that the film was purchased. Information found at 3MGraphics.com/warranties includes:

- [3M Graphics Warranties Bulletin](#)
 - This bulletin contains information on limitations and exceptions, and warranty period reductions for 3M Graphics Warranties. The warranty period may be reduced and stipulations may apply for certain constructions, applications, and graphic exposures as covered in this Bulletin.
- [3M Graphics Warranties Selector](#)
 - Use this selector to search for your vertical warranty period by product type, ink type, film name, and/or ink/prINTER platform.
- [U.S. Desert Southwest Region Map](#)
 - Use this map of hot, arid desert areas to determine if you are subject to reduced warranted durabilities.

The warranties set forth in this Bulletin are made in lieu of all other express or implied warranties, including any implied warranty of merchantability, fitness for a particular purpose, or arising out of a course of dealing, custom, or usage of trade.

3M Basic Product Warranty

3M Graphics Products are warranted to be free of defects in materials and manufacture at the time of shipment and to meet the specifications stated in its applicable 3M Graphics Product Bulletin and as further set forth in the [3M Graphics Warranties Bulletin](#).

Limited Remedy

The limited remedy applicable to each warranty is addressed in the 3M Graphics Warranties Bulletin found at 3MGraphics.com/warranties.

Limitation of Liability

Except where prohibited by law, 3M SHALL NOT UNDER ANY CIRCUMSTANCES BE LIABLE TO PURCHASER OR USER FOR ANY DIRECT (EXCEPT FOR THE LIMITED REMEDY PROVIDED IN THE 3M GRAPHICS WARRANTIES BULLETIN), INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, LABOR, NON-3M MATERIAL CHARGES, LOSS OF PROFITS, REVENUE, BUSINESS, OPPORTUNITY, OR GOODWILL) RESULTING FROM OR IN ANY WAY RELATED TO 3M'S GRAPHICS PRODUCTS, SERVICES, or THIS BULLETIN. This limitation of liability applies regardless of the legal or equitable theory under which such losses or damages are sought.

Additional Limitations

See the 3M Graphics Warranties Bulletin at 3MGraphics.com/warranties, for terms, additional limitations of your warranty, if any, information on reduced warranties for different exposures, and limitations of liability.